

# LINAX<sup>®</sup> DECKING

A sustainable choice of decking with double wood preservation

## WHY LINAX<sup>®</sup>?



**Repels moisture**



**Low Maintenance**  
– required every 5-6 years



**Long Service Life**  
– with 50 years rot protection warranty



**Colour Retention**  
– guaranteed for 12 years



**Dimensionally Stability**



**Active carbon store**  
– Linax decking holds carbon throughout its full lifespan



**Sustainably Sourced Timber**

### DECKING PRODUCT INFORMATION

**SIZE:**  
32x150mm  
(28x145mm actual)

**COLOURS:**  
Brown, Natural, Grey

**LENGTHS:**  
3,6m / 4,2m / 4,8m

**PROFILE NAME:**  
Crossglockner



### REQUIRED (LINAX OIL)

**INSTALLATION:**

Linax oil is required during the installation for warranties to apply. All cut ends and surfaces must be coated with Linax oil.

**MAINTENANCE:**

Linax oil is brushed on to the surface of Linax and left to dry for 24 hours.

**COVERAGE:**

4-6M<sup>2</sup>/L

Only Linax oil can be used on Linax decking, using other oils and stains will invalidate the warranties.

### RECOMMENDED

**DECK JOISTS:**

Deck joists treated to UC4 are recommended for a longer lasting decking substructure.

**SIZE:**  
47x100mm / 47x150mm

**LENGTHS:**

3,6m & 4,8m.

**COLOUR:**  
Brown



Designed to last longer outdoors